




ELITE Timber
Supplies

Sheet Materials




As you'd expect, our sheet materials are practical for both internal and external structural or non-structural purposes to get the desired results for your project.

Products are manufactured from solid or recycled timber and made of timber particles in the form of fibres or veneers, to create versatile wood panels that can be used in almost all forms of construction, interior designs and structural work.



Plywood Sheets

Improved strength and stability to prevent Plywood Sheets from warping and splitting...




MDF Board

MDF Board (Medium Density Fibreboard) has less tendency to split without any grain...



OSB

OSB (Oriental Strand Board) is attractive and has been responsibly sourced, ready for...




Chipboard Sheets

These eco-friendly panels are free of natural defects, resistant to warping and splintering...



Hardboard Sheets

With one smooth side and one coarse side, Hardboard Sheets are much stronger...




Plasterboards

Versatile for insulation and moisture reduction when drywall lining in single or multiple layers...



Fire Rated Board

Designed to be fire resistant whilst withstanding wet and humid conditions...




Specialist Sheet/Board

Reusable sheet or board with textured sides to provide extra stability for concrete formwork...

Plywood Sheets

A versatile, flexible and cost-effective sheet material solution with improved stability. Our Plywood Sheets are durable, with all benefits from using pure wood. These fantastic multipurpose panels are for either internal or external applications with various finishes and thicknesses available.



Types



Hardwood



Softwood

Specifications

Width x Thickness	Lengths
1200mm x 4-25mm	2.4m
Tolerances:	0mm
Species:	Hardwood or Softwood
Profiles:	Square edge
Grading:	EN636-2 / EN636-3
Treatments:	Fire treatment options available

Please visit our website for specific sizes or contact us to find out more on our fire treatment options.



On time

Feel assured with our process and scheduling techniques to deliver products as expected.



Great approach

We are with you every step of the way with communication for a great level of service.



Made to measure

Accuracy is important, so we do our utmost to find right sized items to match the job's requirements.

MDF Board

A lighter alternative than most boards and a practical timber replacement.

Our flexible MDF (Medium-Density Fibre) Board is isotropic, meaning that there is less of a tendency to split without any grain, and manufactured from a mixture of wood fibres, waxes, and resins then hot pressing to different thicknesses.

It follows the contours of any surface when installed, is free of natural defects and smooth sanded for a precision finish.



Specifications

Width x Thickness	Lengths
2440-3050mm x 6-30mm	1.22-1.83m
Tolerances:	0mm
Species:	MDF (Medium-Density Fibre)
Profiles:	Square edge
Grading:	FSC® certified / BS EN 622-H1, EN 622-5, EN 335-3, EN 324-1, EN 321, EN 320, EN 319, EN 318 and EN317
Treatments:	Moisture resistant as standard. Fire treatment options available

Please visit our website for specific sizes or contact us for MDF Boards to improve fire resistance performance.



Properly sourced

Our timber supplies are only from sustainable and reputable UK and European sources.



No minimum order

Order the quantities you need, no matter what the product or your project size.



Expert team

You can count on us! We have a fantastic customer service to demonstrate when you contact us.

OSB

A durable alternative to plywood.
OSB (Oriental Strand Board) is responsibly sourced from European Mills, ready for engineering through wood strand layer compression with adhesives. Added treatment of moisture resistant resins can enhance moisture resistance.



Types



OSB 3



Tongue & Groove

Specifications

Width x Thickness	Lengths
1200-1220mm x 9-18mm	2.4-2.7m
Tolerances:	0mm
Species:	Not applicable
Profiles:	Square edge / Tongue & Groove
Grading:	BS EN 323, EN 324-1, EN 324-2, EN322, EN 321, EN 319, EN 317, EN 310, EN 13986 and EN 120 BBA approved under BS 5268: Part 2, 2002 and Eurocode NHBC technical standards
Treatments:	Moisture resistance or fire treatment

Please visit our website for specific sizes or contact us with your requirements, we can source a vast portfolio of sizes.



Standard delivery

Near or far, we can offer delivery options to dispatch your products within 2 - 5 working days.



Same & next day

We have our own vehicles and work closely with couriers to dispatch your items fast.



Collection

If you are near to our storage depot or want to travel to us, collect your items for free.

Chipboard Sheets

A budget option for versatile furniture, shelving, cabinets and in-building work. Chipboard Sheets (Low-Density Fibreboard) are made from wood chips compressed and laminated with synthetic resin. They are eco-friendly, free of natural defects and resistant to warping and splintering.



Treatments



Waterproof



Slip resistant film



Acoustic

Specifications

Width x Thickness	Lengths
600mm x 18-22mm	2.4m
Tolerances:	0mm
Species:	Not applicable
Profiles:	Square edge / Tongue & Groove
Grading:	FSC® accredited, BBA certification and BS EN 312-5
Treatments:	Waterproof, slip-resistant film, heavy-duty film or acoustic

Please visit our website for specific sizes or contact us with your requirements or to find out more on our treatments.



Construction

Expand, extend or improve an industrial construction



Civil Engineering

Specific materials to complete a design plan



Landscaping

Improve surrounding land with decorative structures



Building

Long lasting, thermal, insulated or fire retardant items

Hardboard Sheets

Multi-purpose sheet panels for flooring and general internal non-structural use. Hardboard Sheets are denser than MDF Boards, with one smooth side and one coarse side for extra grip. Once primed and sealed, they can be painted or vinyl coated.



Treatments



Oil tempered



Moisture Resistant

Specifications

Width x Thickness	Lengths
610-1220mm x 3.2-6mm	1.2-2.44m
Tolerances:	0mm
Species:	Not applicable
Profiles:	Square edge / perforated
Grading:	Not applicable
Treatments:	Oil tempered or moisture resistant

Please visit our website for specific sizes or contact us with your requirements, we can source a vast portfolio of sizes.



UK delivery

All areas of the UK are covered, as well as same or next day delivery available on many products.



Bespoke products

Sometimes standard specifications won't suffice, so our bespoke service is specific to what you're looking for.



Financial advice

Support doesn't have to end after a sale. We care to help you get the results for your project.



Plasterboards

A versatile solution for insulation and moisture reduction when drywall lining within modern buildings.

We have a specific range of Plasterboards to meet many requirements, starting from the standard size of 1200mm wide sheets specifically designed to suit 600mm stud spacing and variable to particular sizes.

Our Plasterboards can be installed in single or multiple layers to create maximum safety and comfort within housing projects and residential environments.



Specifications

Width x Thickness	Lengths
1200mm x 12mm	2.4m
Tolerances:	0mm
Species:	Not applicable
Profiles:	Square edge / tapered
Grading:	Not applicable
Treatments:	Not applicable

Please contact us for Plasterboards to reduce noise transmission or improve fire resistance performance.



UK delivery

All areas of the UK are covered, as well as same or next day delivery available on many products.



Bespoke products

Sometimes standard specifications won't suffice, so our bespoke service is specific to what you're looking for.



Financial advice

Support doesn't have to end after a sale. We care to help you get the results for your project.

Fire Rated Board

Increased fire protection with Euroclass B & C for domestic separating walls, garages, corridors and timber floors.

Our Fire Rated Board is non-combustible and adapted for drylining, wall lining and ceiling systems whilst holding stability within damp conditions and resistance to mould growth.



Types



Hardwood



Softwood

Specifications

Width x Thickness	Lengths
1220mm x 7-30mm	2.4-3.1m
Tolerances:	0mm
Species:	Hardwood or Softwood
Profiles:	Square edge
Grading:	PEFC™ and FSC® approved - check our website for more information
Treatments:	Fire rated and enhanced to Euroclass B & C

The above dimensions are for our standard option, for B S2 d0 only options please visit our website for specifications.



On time

Feel assured with our process and scheduling techniques to deliver products as expected.



Great approach

We are with you every step of the way with communication for a great level of service.



Made to measure

Accuracy is important, so we do our utmost to find right sized items to match the job's requirements.

Specialist Sheet/Board

Produce an exceptional finish with MDO (Medium Density Overlay) plywood. Our Specialist Sheet/Board is FSC certified, strong to the core and available with a thin and thick layer either side. Its properties make it ideal to be reused for concrete formwork.



Types



Hardwood



Softwood

Specifications

Width x Thickness	Lengths
1220mm x 18mm	2.4m
Tolerances:	0mm
Species:	Hardwood or Softwood
Profiles:	Square edge
Grading:	FSC® approved and grading available
Treatments:	Various treatments available – contact us to find out more

Please visit our website for specific sizes or contact us with your requirements, we can source a vast portfolio of sizes.



Standard delivery

Near or far, we can offer delivery options to dispatch your products within 2 - 5 working days.



Same & next day

We have our own vehicles and work closely with couriers to dispatch your items fast.



Collection

If you are near to our storage depot or want to travel to us, collect your items for free.